

NUPOWER™

C-BAND SOLID STATE POWER AMPLIFIER

NuWaves
Engineering

FEATURES

- 15 Watts Typical
- 4 GHz to 6.1GHz
- 0 dBm Nominal RF Input
- High Power SSPA
- GaN Technology
- Small Form Factor (3.9 cubic inches)
- High Efficiency
- Single Power Supply
- Over Voltage Protection
- Reverse Voltage Protection
- Thermal Protection
- Logic On/Off Control
- External Heatsink Available
- SMA Connectors
- C-Band PA Kit available that includes SSPA, Heatsink, Power Cables, and External Isolator

If you have other requirements, NuWaves provides state-of-the-art RF design services to customize products to your needs.

NuWaves Engineering
Research & Technology Center
122 Edison Drive
Middletown, Ohio 45044
(513)360-0800
Fax (513)360-0888

product.sales@nuwaves-ltd.com
www.nuwaves-ltd.com

NW-SSPA-15W-4.0-6.1

NuWaves' NW-SSPA-15W-4.0-6.1 is a high performance solid state power amplifier delivering 15 watts across the frequency band of 4 GHz to 6.1 GHz.



The small form factor of 3.9 cubic inches brings state-of-the-art miniature power amplifier technology to the warfighter, meeting present challenges in size and weight reduction.

The NuPower™ NW-SSPA-15W-4.0-6.1 is ideal for broadband RF telemetry and military communication systems that require high reliability and high efficiency in a compact housing.

For additional information, contact NuWaves by email at product.sales@nuwaves-ltd.com or by phone at (513)360-0800.

CHARACTERISTICS

Operational:

Frequency Range.....	4 GHz to 6.1 GHz
RF Output Power.....	15 watts Typical
RF Gain.....	43 dB
2nd Harmonic.....	-13 dBc
Noise Figure.....	3.7 dB
Power Supply.....	20-32 Vdc
Power Consumption	
High Pwr Transmit.....	2.7A max @ 28Vdc
Power Amplifier Enable.....	GND On
Input/Output VSWR.....	< 2:1

Mechanical:

Size.....	3.0" x 2.0" x 0.65" (LxWxH)
Weight.....	3 oz

Environmental:

Operating Temperature.....	-40 to +85 °C
Storage Temperature.....	-40 to +85 °C